



TECHNICAL PARAMETERS

Name		Data
BASIC	Operating Weight	14000kg
	Weight Burden on Drum	7000 kg
	Weight Burden on Wheel	7000 kg
	Min Ground Clearance(h)	420mm
	Wheelbase (L1)	3100mm
	Grade Ability	30%
	L×W1×H (mm)	5975×2280×3278
ENGINE	Manufacturer	WEI CHAI
	Model	WP6G125E202
	Displacement	5.9L
	Fuel consumption	28.3L
	Rated Power	92 kW
	Rated Speed	2000 rpm
DRIVE TRAIN	Emissions Standard	Nation II
	Drive Type	Mechanical Drive
	Travel Speed Forward	2.32/4.1/11.38 km/h
	Travel Speed Reverse	2.32/4.1 km/h
	Tire Type	23.1-26 12PR
	Min.Turning Radius	6300 mm
	Steering Angle	30 °
VIBRATION SYSTEM	Swing Angle	10 °
	Width of Drum (W2)	2120 mm
	Diameter of Drum	1520 mm
	Rim Thickness of Drum	30 mm
	Static Linear Load	330N/cm
	Vibration Type	Open-loop Hydraulic
	Centrifugal Force	290/160 kN
BRAKE SYSTEM	Vibration Frequency	28 Hz
	Nominal Amplitude	1.8/0.9 mm
	Service Brake	Air Booster Caliper Rear Axle Brake
ELECTRIC	Parking Brake	Shaft Controlling Brake of Gear Box
	Voltage	24 V
SERVICE REFILL CAPACITY	Capacity	120×2 Ah
	Fuel Tank Capacity	240 L
	Hydraulic Tank Capacity	240 L

CONFIGURATION

WEI CHAI Engine
Machanical Transmission
Dry-type Drive Axle
Open-loop Hydraulic Vibration System
ROPS/FOPS
Air Conditioner
Standard Steering System

OPTIONAL

WEI CHAI Engine (Nation III)
Cold Start
Coated Cams
Pressure Measuring Tie-in

PRODUCT FEATURES

Single frequency, dual amplitude, open-loop vibratory roller, PERMCO hydraulic components.
Steel drum made of high strength metal material with well wear resistance impress resistance.
Panoramic cab, angle-adjustable steering wheel, the design according to ergonomics.
Two brake systems containing hand brake and foot brake to make sure the safety of operator and machine.
Engine hood is opened backward through manual operation and oil cylinder booster , large space for repair and maintenance.
Equiped with A/C system as standard to make operating environment comfortable.

Lonking 龙工

Code:10501403250

CDM514B

B SERIES SINGLE DRUM VIBRATORY ROLLERS

Efficiency Rules the Future



For more information on Lonking products,
Please contact our local agent:

The following blank can be used for notes or comments.

Lonking (Fu Jian) International Trade Co., Ltd.

Lonking Holdings Limited

Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai

Tel: +86-21-3760 2242

E-mail:export@lonking.cn

<http://www.lonkinggroup.com>

- **RATED POWER:** 92kW/2000rpm
- **OPERATING WEIGHT:** 14000kg
- **STATIC LINEAR LOAD:** 330N/cm
- **DRUM / TIRE LOAD:** 7000/7000kg