



TECHNICAL PARAMETERS

	ITEM	UNIT	CDM6306
Basic	Operating weight	kg	32800
	Boom length	mm	6150
	Arm length	mm	3200
	Standard bucket	m³	1.6（Rock）
	Max.Travel speed	km/h	3.4-5.2
	Max.Swing speed	rpm	9.5
	Grade ability	°	35(70%)
	Ground pressure	kPa	62
	Max.Traction force	kN	283
Engine	Engine model	——	GH-6HK1
	Rated power	kW/rpm	212/2000
	Max.Torque	Nm/rpm	1080/1500
	Displacement	L	7.79
	Fuel tank	L	600
Hydraulic	Max.Flow(total)	L/min	288×2
	Max.Working pressure	MPa	34.3
	Max.Pilot pressure	MPa	3.9
	Max.Arm digging force	kN	170
	Max.Bucket digging force	kN	220
	Hrdraulic oil tank	L	300
Chassis	Track width	mm	600
	Track shoes number	——	47×2
	Carrier rollers number	——	2×2
	Track rollers number	——	8×2
Electric	System vollage	V	24
	Battery capacity	V/Ah	24/165×2

PRODUCT FEATURES

Isuzu Turbocharged Engine, Large Displacement, Strong Power
Optimized Cooling System to Reduce Power Loss and Noise
Advanced Control System
Combined C type closed frame improves rigidity and strength of rotary platform.
Camfortable ROPS Cabin with 2.7m³ Operational Space
No Frame Cab Glasses to Enlarge Operation Field of View
Rock Track Shoes, Chassis Reinforcement, More reliable and Wear-resistant
Heavy-duty Working Device with High Strength Low Alloyed Steels

OPTIONAL

Breaking hammer & pipeline
Work warning light
Walking alarm
Top protecting net
Front protecting net
700mm triple grouser shoes
800mm triple grouser shoes

For more information on Lonking products,
Please contact our local agent:

The following blank can be used for notes or comments.

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not be used without written permission.
2023/01

Specifications and design are subject to change without prior notice.
Machines shown may not include optional accessories.

Lonking 龙工

CDM6306
HYDRAULIC EXCAVATOR

Efficiency Rules the Future



- OPERATING WEIGHT: 32800kg
- ENGINE POWER: 212kW
- BUCKET CAPACITY: 1.6m³
- TRAVEL SPEED: 3.4/5.2km/h

Lonking (Fu Jian) International Trade Co., Ltd.
Lonking Holdings Limited
Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai
Tel: +86-21-3760 2242 E-mail:export@lonking.cn
<http://www.lonkinggroup.com>