



TECHNICAL PARAMETERS

	Name	Data
BASIC	Operating Weight	20000 kg
	Weight Burden on Drum	10000 kg
	Weight Burden on Wheel	10000 kg
	Min Ground Clearance(h)	430 mm
	Wheelbase (L1)	3180 mm
	Grade Ability	30%
	L×W1×H (mm)	6260×2388×3200
ENGINE	Manufacturer	WEI CHAI
	Model	WP6G175E301
	Displacement	6.75L
	Fuel consumption	29.2L
	Rated Power	129 kW
	Rated Speed	2000 rpm
	Emissions Standard	Nation III
	Drive Type	Mechanical Drive
	Travel Speed Forward	2.3/4.5/9.6 km/h
DRIVE	Travel Speed Reverse	2.3/4.5/9.6 km/h
TRAIN	Tire Type	20.5-25-16PR
TRAIN	Min.Turning Radius	6500 mm
	Steering Angle	33°
	Swing Angle	/
VIBRATION SYSTEM	Width of Drum (W2)	2130 mm
	Diameter of Drum	1600 mm
	Rim Thickness of Drum	40 mm
	Static Linear Load	469N/cm
	Vibration Type	Open-loop Hydraulic Vibration
	Centrifugal Force	356/248 kN
	Vibration Frequency	28 Hz
	Nominal Amplitude	1.9/0.9 mm
BRAKE SYSTEM	Service Brake	Air Booster Caliper Rear Axle Brake
	Parking Brake	Shaft Controlling Brake of Gear Box
ELECTRIC	Voltage	24 V
	Capacity	120×2 Ah
SERVICE REFILL CAPACITY	Fuel Tank Capacity	335 L
	Hydraulic Tank Capacity	220 L

CONFIGURATION		
VEI CHAI Engine		
Mechanical Gear shifting Transmission		
ONKING Drive Axle		
Open-loop Hydraulic Vibration system		
ROPS/FOPS		
Air Conditioner		
Standard Steering System		

	OPTIONAL		
	Cold Start		
on	Coated Cams		

Pressure Measuring Tie-in

PRODUCT FEATURES

Single frequency, dual amplitude, open-loop vibratory roller, PERMCO hydraulic components.

Steel drum made of high strength metal material with well wear resistance impress resistance.

Panoramic cab, angle-adjustable steering wheel, the design according to ergonomics.

Two brake systems containing hand brake and foot brake to make sure the safety of operator and machine.

Engine hood is opened backward by the electrically controlled cylinder , large space for repair and maintenance.

Equiped with A/C system as standard to make operating environment comfortable.



CDM520B9 B SERIES SINGLE DRUM VIBRATORY ROLLERS

Efficiency Rules the Future



The following blank can be used for notes or comments.

For more information on Lonking products, Please contact our local agent:

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not 2022/12 ed without written per

Specifications and design are subject to change without prior notice. s shown may not incl

LONKING (FU JIAN) INTERNATIONAL TRADE CO., LTD.

LONKING HOLDINGS LIMITED

Add:26 Minyi Road, Xinqiao, Songjiang Industrial Zone, Shanghai Tel: +86-21-3760 2242 E-mail:export@lonking.cn http://www.lonkinggroup.com

Code:10502004070



RATED POWER: 129kW/2000rpm **OPERATING WEIGHT:** 20000kg STATIC LINEAR LOAD: 469N/cm DRUM / TIRE LOAD: 10000/10000kg